

# TYPE APPROVAL CERTIFICATE

**This is to certify:****That the Electric Power Cable**with type designation(s)  
**HELUTHERM 145**

Issued to

**Helukabel GmbH**  
**Hemmingen, Germany**is found to comply with  
**DNV GL rules for classification – Ships, offshore units, and high speed and light craft****Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****Rated voltage (kV) 0,3/0,5 0,45/0,75 and 0,6/1**  
**Temp. class (°C) 120**Issued at **Hamburg** on **2020-09-08**for **DNV GL**This Certificate is valid until **2025-09-07**.DNV GL local station: **Augsburg**Approval Engineer: **Carsten Hunsalz**

---

**Arne Schaarmann**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Job Id: 262.1-024772-2  
Certificate No: TAE000029A  
Revision No: 1

## Product description

Halogen-free, low smoke cable with resistance against heat

Type: HELUTHERM 145

Rated voltage: U0/U = 300/500 V < 1,0 mm<sup>2</sup>  
U0/U = 470/750 V > 1,5 mm<sup>2</sup>  
U0/U = 600/1000 V > 1,5 mm<sup>2</sup> (fixed and protected installation)

Operating temperature: -40° C to +120° C (20 000 h)

Conductor: Tinned or plain copper, acc. IEC 60228 (except Class 1)

Core insulation: EI5 Cross-linked Polyolefin acc. EN 50363-5

Braid / screen : Copper tinned (optional)

Outer sheath : EM10 Cross-linked Polyolefin acc. EN 50363-6

No. of cores: Nominal cross section mm<sup>2</sup>

1	0,5 up to 240
1 to 37	0,5 up to 2,5
1 to 14	4
1 to 7	6 up to 25
1 to 5	35 up to 95

screened version

1 to 21	0,5 up to 2,5
1 to 14	4
1 to 7	6 and 10

## Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

## Type Approval documentation

Test reports: Helukabel: 22.04.2010;  
VDE 1519100-5920-0070/104041: 15.12.2008  
MPA 2009-B-2623/03 // 3812: 07.07.2009 // 21.09.2009  
MPA 2010-B-2175: 06.07.2010

Data sheet: HELUTHERM 145: 2010-02-25

## Tests carried out

Standard	Release	General description	Limitation
UL 758	2014	Appliance Wiring Material	
IEC 60228	2004-11	Conductors of insulated cables	
EN 50363-5	2006-10	Insulating, sheathing and covering materials for low voltage energy cables - Part 5: Halogen-free, cross-linked insulating compounds	
EN 50363-6	2006-10	Insulating, sheathing and covering materials for low voltage energy cables - Part 6: Halogen-free, cross-linked sheathing compounds	

Job Id: 262.1-024772-2  
Certificate No: TAE000029A  
Revision No: 1

Standard	Release	General description	Limitation
EN 60216-2	2006-04	Electrical insulating materials - Thermal endurance properties - Part 2: Determination of thermal endurance properties of electrical insulating materials	
IEC 60332-1-2	2015-07	Tests on electric and optical fibre cables under fire conditions. Part 1-2. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame	
IEC 60332-3-22	2018-07	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 61034-1/2	2013-06	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Light transmittance >60%

## Marking of product

HELUKABEL - HELUTHERM 145 - voltage - size - IEC 60332-3-22 - DNV GL TAE000029A Rev.1 - HALOGEN-FREE acc. IEC 60754-1/2 - CE  
(Additional marking e.g. article no., order no., meter marker is permitted)

## Place of Production

HELUKABEL GmbH, Werk Windsbach

## Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.  
END OF CERTIFICATE