



Style 1569 - APPLIANCE WIRING MATERIAL

APPLIANCE WIRING MATERIAL

Subj. 758
Section 1
Page 1569

Issued: 1972-09-26
Revised: 2013-02-22

Style 1569 Single Conductor with extruded insulation

RATING 80, 90 or 105 deg C, 300 Vac, Horizontal flame.

CONDUCTOR 30 AWG - 2 AWG, solid or stranded.

INSULATION Extruded PVC.

Conductor size	Minimum average thickness	Minimum thickness at any point
30-10 AWG	15 mils	13 mils
9-2 AWG	30 mils	27 mils

COVERING Optional, Extruded PVC, 9 mils minimum average thickness, 8 mils minimum thickness at any point.

STANDARD Appliance Wiring Material UL 758.

MARKING General.

USE Internal wiring of appliances or electronic equipment where not subjected to movement or mechanical damage. Tag may also indicate the following, "600 Volts Peak for Electronic Use Only."

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"